Product name:
 PROLAN EXTREME
 Page:
 1/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: PROLAN EXTREME
Container size: 1 I, 5 I, 10 I, 200 I.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Lubricant.

Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet

Supplier: Denrex ApS

Daniavej 33, Assens DK- 9550 Mariager Tel: +45 24428188 In@denrex.com www.denrex.com

Responsible for safety data

sheet authoring:

In@denrex.com

1.4. Emergency telephone number

Emergency telephone: Poison Control Centers may be available in specific member countries.

+45 24428188 (Only during office hours)

 Product name:
 PROLAN EXTREME
 Page:
 2/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

<u>CLP:</u> Skin Irrit. 2;H315 - Eye Irrit. 2;H319 - STOT SE 3;H336 - Asp. Tox. 1;H304 -

Aquatic Chronic 3;H412

2.2. Label elements



Danger

Contains: Naphtha (petroleum), hydrotreated heavy and Distillates (petroleum),

hydrotreated light; Kerosine-unspecified

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P260 Do not breathe vapour/spray.

P280 Wear eye protection and gloves.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: Lanolin, wax and organic solvent.

CLP:

<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	Chemical name:	Hazard classification:	Notes:
30-60	64742-48-9	265-150-3	-	Naphtha (petroleum), hydrotreated heavy	Eye Irrit. 2;H319 STOT SE 3;H336 Asp. Tox. 1;H304	
10-20	64742-47-8	265-149-8	-	Distillates (petroleum), hydrotreated light; Kerosine- unspecified	STOT SE 3;H336 Asp. Tox. 1;H304 Aquatic Chronic 2;H411	

References: The full text for all hazard statements is displayed in section 16.

Product name:PROLAN EXTREMEPage:3/9Supersedes date:2019-04-07Revision:2020-08-11Product No.:SDS-ID:EU-EN/2.0

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move injured person into fresh air and keep person calm under observation. If

uncomfortable: Seek hospital and bring along these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water.

In case of eczema or other skin disorders: Seek medical attention and bring

along these instructions.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any

contact lenses and open eyelids widely. If irritation persists: Seek medical

attention and bring along these instructions.

<u>Ingestion:</u> Immediately rinse mouth and drink plenty of water. Keep person under

observation. If person becomes uncomfortable seek hospital and bring these instructions. Do not induce vomiting. If vomiting occurs, keep head low so that

stomach content doesn"t get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: Be aware that symptoms of lung oedema (shortness of breath) may develop up

to 24 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire- Selection of respiratory protection for fire fighting: follow the general fire

<u>fighters:</u> precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid inhalation of vapours and contact with skin and eyes. Follow precautions

for safe handling described in this safety data sheet.

6.2. Environmental precautions

<u>Environmental</u> Avoid discharge into drains, water courses or onto the ground.

precautions:

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb spillage with oil-absorbing material. Clean contaminated area with oil-

removing material. In case of spills, beware of slippery floors and surfaces.

6.4. Reference to other sections

References: For personal protection, see section 8.

For waste disposal, see section 13.

Product name:PROLAN EXTREMEPage:4/9Supersedes date:2019-04-07Revision:2020-08-11Product No.:SDS-ID:EU-EN/2.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Avoid inhalation of vapours and

contact with skin and eyes.

<u>Technical measures:</u> Work practice should minimise contact. Avoid smoking and use of open fire.

Technical precautions: Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> Follow rules for flammable liquids.

storage:

Storage conditions: Store in tightly closed original container in a cool and well-ventilated place.

7.3. Specific end use(s)

Specific use(s): Not relevant.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Please note that there may be national occupational exposure limits.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and

minimise the risk of inhalation of vapours and spray mist.

Provide access to washing facilities incl. soap, skin cleanser and fatty cream.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable

respiratory equipment. Use respiratory equipment with gas filter, type A2.

Hand protection: Risk of contact: Wear protective gloves. Nitrile gloves are recommended, but

be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in collaboration with the supplier of gloves, who can inform about the breakthrough time of the glove

material.

Eve protection: Risk of splashes: Wear goggles/face shield.

Skin protection: Wear apron or protective clothing in case of contact.

<u>Hygiene measures:</u> Wash hands after handling. Change contaminated clothing.

 Product name:
 PROLAN EXTREME
 Page:
 5/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Form: Liquid.

Colour:Light brown.Odour:Characteristic.pH:Not available.Melting point / freezing point:Not available.Boiling point:Not available.

Flash point: 66 °C
Evaporation rate: < 1

Explosion limits: Not available.

Vapour pressure: Not available.

<u>Vapour density:</u> > 1

Relative density: 0,81 - 0,83 g/ml

Solubility: Immiscible with water.

<u>Auto-ignition</u> Not available.

temperature (°C):

Viscosity: < 20 mm2/s (40 °C)

9.2. Other information

Other data: Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: None known.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

<u>Hazardous Reactions:</u> None known.

10.4. Conditions to avoid

<u>Conditions/materials to avoid:</u> Avoid exposure to high temperatures or direct sunlight. Keep away from heat,

sparks and open flame.

10.5. Incompatible materials

Incompatible materials: Strong alkalis. Strong oxidising agents. Galvanized steel. Mild steel. Zinc.

10.6. Hazardous decomposition products

Hazardous decomposition

None in particular.

products:

Product name: PROLAN EXTREME 6/9 Page: Supersedes date: 2019-04-07 2020-08-11 Revision: Product No.: SDS-ID: EU-EN/2.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met. Acute Toxicity (Dermal): Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Acute Toxicity (Inhalation):

Skin Corrosion/Irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin

Reproductive Toxicity:

sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: May cause drowsiness or dizziness.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Vapours and spray mist may irritate throat and respiratory system and cause Inhalation:

> coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Irritating and degreasing. Skin contact:

Eye contact: Irritating and may cause redness and pain.

Ingestion: May cause nausea, headache, dizziness and intoxication.

Droplets of the product aspirated into the lungs through ingestion or vomiting

may cause a serious chemical pneumonia.

Specific effects: Frequent inhalation of even small concentrations may cause irritability, fatigue

and memory failure and eventually permanent damage to the nervous system,

including the brain.

Toxicological data: Naphtha (petroleum), hydrotreated heavy:

> Acute Toxicity (Oral LD50): > 4500 mg/kg Acute Toxicity (Dermal LD50): > 1900 mg/m³ Acute Toxicity (Inhalation LC50): 8,4 mg/l (4 hours)

Distillates (petroleum), hydrotreated light; Kerosine-unspecified:

Acute Toxicity (Oral LD50): > 5000 mg/kg Acute Toxicity (Dermal LD50): > 2000 mg/m3

 Product name:
 PROLAN EXTREME
 Page:
 7/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

<u>Ecotoxicity:</u> Harmful to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated heavy:

LC50 96 hours, fish, mg/l: 4,1 EC50 48 hours, Daphnia, mg/l: 4,5

EC50 (algae, 72h): > 1

Distillates (petroleum), hydrotreated light; Kerosine-unspecified:

LC50 96 hours, fish, mg/l: 1,13 EC50 48 hours, Daphnia, mg/l: 2 EC50 (algae, 72h): 1,714

12.2. Persistence and degradability

<u>Degradability:</u> The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

<u>PBT/vPvB:</u> This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Other adverse effects: The product contains volatile, organic compounds which have a photochemical

ozone creation potential.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 20 01 26

 Product name:
 PROLAN EXTREME
 Page:
 8/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No:

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

Class: -

14.4. Packing group

PG: -

14.5. Environmental hazards

Marine pollutant:

Environmentally Hazardous

substance:

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation:

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.

Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work, with amendments.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work, with amendments.

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives, with amendments. 2014/955/EC: Commission Decision of 18 December 2014 amending Decision 2000/532/EC as regards the list of wastes.

15.2. Chemical Safety Assessment

<u>CSA status:</u> No chemical safety assessment has been carried out.

 Product name:
 PROLAN EXTREME
 Page:
 9/9

 Supersedes date:
 2019-04-07
 Revision:
 2020-08-11

 Product No.:
 SDS-ID:
 EU-EN/2.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 2, 6, 7, 8.

<u>Abbreviations and acronyms</u> PBT = Persistent, Bioaccumulative and Toxic. <u>used in the safety data sheet:</u> vPvB = very Persistent and very Bioaccumulative.

CSA = Chemical Safety Assessment.

LD50 = Lethal Dose 50%.

EC50 = Effective Concentration 50%. LC50 = Lethal Concentration 50%.

Additional information: Classification according to Regulation (EC) No. 1272/2008:

Calculation method.

Wording of H-statements:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.